



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name MAINTENANCE SPRAY

Product No. K033

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses multi-purpose plant and automotive spray

1.3. Details of the supplier of the safety data sheet

Selden Research Limited t : 01298 26226 Staden Lane Ashbourne Road f : 01298 26540

e: safety@selden.co.uk

Buxton
Derbyshire
SK17 9RZ
United Kingdom

1.4. Emergency telephone number

01298 26226

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (67/548/EEC) F+;R12. R66.

2.2. Label elements

Labelling



Extremely Flammable

Risk Phrases R12 Extremely flammable., R66 Repeated exposure may cause skin dryness or cracking.

Safety Phrases S16 Keep away from sources of ignition - No smoking.

S51 Use only in well-ventilated areas. S2 Keep out of the reach of children.

S23 Do not breathe vapour/spray., A1 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use., A2 Do not spray on a naked flame or any

incandescent material.

2.3. Other hazards

PRESSURISED CONTAINER - increase in temperature to greater than 50C will cause internal pressure to rise potentially causing bursting/explosion.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not Applicable

3.2. Mixtures

ALIPHATIC DISTILLATE 30-60%

CAS-No.: 64742-48-9 EEC (EINECS) No. 265-150-3

Classification (EC 1272/2008) Classification (67/548/EEC)
Aspiration hazard, category 1 - H304 Xn;R65

Flammable liquids, category 3 - H226 R10,R66

Repeated exposure may cause skin dryness or cracking - EUH066

MSDS: K033 - MAINTENANCE SPRAY language: english Page 1 of 5







10-30%

BUTANE

CAS-No.: 106-97-8 EEC (EINECS) No. 203-448-7 Classification (EC 1272/2008) Classification (67/548/EEC)

Flammable liquids, category 1 - H224 F+;R12

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information Treat Symptomatically

Inhalation Move the exposed person to fresh air at once., Keep the affected person warm and at rest. Get prompt medical

attention., For breathing difficulties oxygen may be necessary.

Ingestion Rinse mouth thoroughly., Drink plenty of water., Get medical attention.

Skin contact Wash the skin immediately with soap and water., Get medical attention if any discomfort continues.

Promptly wash eyes with plenty of water while lifting the eye lids., Continue to rinse for at least 15 minutes., Get Eye contact

medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and

vomiting., Gas or vapour displaces oxygen available for breathing (asphyxiant)., Unconsciousness.

May cause burns in mucous membranes, throat, oesophagus and stomach., May cause stomach pain or Ingestion

Skin contact May cause defatting of the skin, but is not an irritant., Repeated exposure may cause skin dryness or

cracking

Eye contact Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat Symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media Use:, Powder., Dry chemicals, sand, dolomite etc., Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

Unsuitable extinguishing media

5.3. Advice for firefighters

Special Fire Fighting

Procedures

Self contained breathing apparatus and full protective clothing must be worn in case of fire. Containers close to fire should be removed or cooled with water., Use water to keep fire exposed containers cool and

disperse vapours.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

For personal protection, see section 8

6.2. Environmental precautions

Any spillage needs to be contained and not allowed to enter water courses

6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment., Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate., If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections

MSDS: K033 - MAINTENANCE SPRAY language: english Page 2 of 5





For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Keep away from heat, sparks and open flame., Avoid spilling, skin and eye contact., Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)

See product label for detailed usage and instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

 Name
 STD
 TWA - 8 Hrs
 STEL - 15 Min
 Notes

 BUTANE
 WEL
 600 ppm1450 mg/m3
 750 ppm1810 mg/m3

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Engineering measures Provide adequate general and local exhaust ventilation.

Hand protection Use protective gloves.

Eye protection Wear approved safety goggles.

Other Protection General workwear only

Hygiene measures DO NOT SMOKE IN WORK AREA!

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Comments Information given relates to total aerosol container contents.

Relative density 0.664 @ 20 °C

Flash point (°C) - 74
Auto Ignition Temperature (°C) + 405
Flammability Limit - Upper(%) 1.8
Flammability Limit - Lower(%) 10.0

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Stable under normal temperature conditions.

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

None known

10.4. Conditions to avoid

MSDS: K033 - MAINTENANCE SPRAY language: english Page 3 of 5







Avoid heat, flames and other sources of ignition., Increase in temperature to greater than 50 degrees will cause rise in internal pressure with likelihood of bursting/explosion.

10.5. Incompatible materials

None known

10.6. Hazardous decomposition products

Fire creates:, Toxic gases/vapours/fumes of:, Carbon monoxide (CO)., Carbon dioxide (CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Toxicological information No toxicological data is available for this mixture, however data can be provided for specific raw materials upon

equest

Inhalation High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and

vomiting., Gas or vapour displaces oxygen available for breathing (asphyxiant)., Unconsciousness.

Ingestion May cause burns in mucous membranes, throat, oesophagus and stomach., May cause stomach pain or vomiting. Skin contact May cause defatting of the skin, but is not an irritant., Repeated exposure may cause skin dryness or cracking.

Eye contact Irritation of eyes and mucous membranes.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Not classed as Hazardous to the Environment but release to the environment should be avoided.

12.2. Persistence and degradability

Degradability The product is biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

Mobility: The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or PvB substances

12.6. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard., Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

 UN No. (ADR/RID/ADN)
 1950

 UN No. (IMDG)
 1950

 UN No. (ICAO)
 1950

14.2. UN proper shipping name

MSDS: K033 - MAINTENANCE SPRAY language: english Page 4 of 5



K033

Proper Shipping Name: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR/RID/ADN Class 2 Class Code:5F Label: 2.1

IMDG Class

1CAO Class/Division

2.1

2.1

Transport Labels Not Applicable

14.4. Packing group

IMDG Packing group N/A ICAO Packing group N/A

14.5. Environmental hazards

Environmentally Hazardous substance/Marine Pollutant No

14.6. Special precautions for user

Tunnel Restriction Code n/a

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not relevant

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

UK Regulatory References The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.

Environmental Listing Rivers (Prevention of Pollution) Act 1961., Control of Pollution (Special Waste Regulations) Act 1980.

Control of Substances Hazardous to Health., The Chemicals (Hazard Information and Packaging for Supply)

Statutory Instruments Regulations 2009 (S.I. 2009 No. 716).

Approved Code Of Practice Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes Workplace Exposure Limits EH40., Introduction to Local Exhaust Ventilation HS(G)37., CHIP for everyone HSG

(108)

(108).
System of specific information relating to Dangerous Preparations. 2001/58/EC., Dangerous Preparations Directive

1999/45/EC., Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives

91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments., Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending

Regulation (EC) No 1907/2006 with amendments.

National Regulations The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007).

15.2. Chemical Safety Assessment

No chemical assessment has been carried out as this Safety Data Sheet is for a mixture

SECTION 16: OTHER INFORMATION

General information

EU Legislation

The following risk phrases relate to the raw materials in the product and not the product itself:-

Revision Comments

Safety Data Sheet revised to be in accordance with EU Regulation No 453/2010 - REACH Regulations.

Revision Date 05/03/2011

Revision 11

Risk Phrases In Full R12 Extremely flammable. | R10 Flammable., R66 Repeated exposure may cause skin dryness or cracking., R65

Harmful: may cause lung damage if swallowed.

Hazard Statements In Full H224 Extremely flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

MSDS: K033 - MAINTENANCE SPRAY language: english Page 5 of 5