



# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name SILICONE LUBRICANT

Product No. KOO7

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Silicone oil., Lubricant.

# 1.3. Details of the supplier of the safety data sheet

Selden Research Limited t : 01298 26226 Staden Lane Ashbourne Road f : 01298 26540

e: safety@selden.co.uk

Derbyshire SK17 9RZ United Kingdom

**Buxton** 

#### 1.4. Emergency telephone number

01298 26226

## SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Classification (67/548/EEC) F+;R12.

# 2.2. Label elements

Labelling



Extremely Flammable

Risk Phrases R12 Extremely flammable.

Safety Phrases A1 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce

or burn, even after use., A2 Do not spray on a naked flame or any incandescent material.

S2 Keep out of the reach of children.

S16 Keep away from sources of ignition - No smoking.

S23 Do not breathe vapour/spray. S51 Use only in well-ventilated areas.

## 2.3. Other hazards

PRESSURISED CONTAINER - increase in temperature to greater than 50C will cause internal pressure to rise potentially causing bursting/explosion.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

## 3.1. Substances

Not Applicable

# 3.2. Mixtures

BUTANE		60-100%
CAS-No.: 106-97-8	EEC (EINECS) No. 203-448-7	
Classification (EC 1272/2008)		Classification (67/548/EEC)
Flammable liquids, category 1 - H224		F+;R12
ISOPARAFFINIC HYDROCARBONS		5-10%
CAS-No.: 90622-57-4	EEC (EINECS) No. 292-459-0	
Classification (EC 1272/2008)		Classification (67/548/EEC)

MSDS: K007 - SILICONE LUBRICANT language: english Page 1 of 5









Aspiration hazard, category 1 - H304 Flammable liquids, category 3 - H226

Hazardous to the aquatic environment, chronic, category 2 - H411 Repeated exposure may cause skin dryness or cracking - EUH066 R10,R53,R66

Xn; R65

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### SECTION 4: FIRST AID MEASURES

#### 4.1. Description of first aid measures

General information Treat Symptomatically.

Inhalation Move the exposed person to fresh air at once., Keep the affected person warm and at rest. Get prompt medical

attention., For breathing difficulties oxygen may be necessary.

Ingestion Rinse mouth thoroughly., Drink plenty of water., Get medical attention.

Skin contact Wash the skin immediately with soap and water., Get medical attention if any discomfort continues.

Eye contact Promptly wash eyes with plenty of water while lifting the eye lids., Continue to rinse for at least 15 minutes., Get

medical attention if any discomfort continues.

#### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and

vomiting., Gas or vapour displaces oxygen available for breathing (asphyxiant)., Unconsciousness.

Ingestion May cause burns in mucous membranes, throat, oesophagus and stomach., May cause stomach pain or

vomiting

Skin contact No specific health warnings noted.

Eye contact Irritation of eyes and mucous membranes.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat Symptomatically.

#### SECTION 5: FIREFIGHTING MEASURES

## 5.1. Extinguishing media

Extinguishing media Use:, Powder., Dry chemicals, sand, dolomite etc., Water spray, fog or mist.

#### 5.2. Special hazards arising from the substance or mixture

Unsuitable extinguishing media

#### 5.3. Advice for firefighters

Special Fire Fighting

Procedures

Self contained breathing apparatus and full protective clothing must be worn in case of fire. Containers close to fire should be removed or cooled with water., Use water to keep fire exposed containers cool and

disperse vapours.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

# 6.1. Personal precautions, protective equipment and emergency procedures

For personal protection, see section 8.

#### 6.2. Environmental precautions

Any spillage needs to be contained and not allowed to enter water courses

## 6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment., Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate., If leakage cannot be stopped, evacuate area.

## 6.4. Reference to other sections

For personal protection, see section 8. For waste disposal, see section 13.

MSDS: K007 - SILICONE LUBRICANT language: english Page 2 of 5





## SECTION 7: HANDLING AND STORAGE

## 7.1. Precautions for safe handling

Keep away from heat, sparks and open flame., Avoid spilling, skin and eye contact., Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

## 7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

#### 7.3. Specific end use(s)

See product label for detailed usage and instructions.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

 Name
 STD
 TWA - 8 Hrs
 STEL - 15 Min
 Notes

 BUTANE
 WEL
 600 ppm1450 mg/m3
 750 ppm1810 mg/m3

WEL = Workplace Exposure Limits

#### 8.2. Exposure controls

Protective equipment



Engineering measures Provide adequate general and local exhaust ventilation.

Hand protection Use protective gloves

Eye protection Wear approved safety goggles.

Other Protection General workwear only

Hygiene measures DO NOT SMOKE IN WORK AREA!

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Comments Information given relates to total aerosol container contents.

Flash point (°C) - 74

Auto Ignition Temperature (°C) + 405

Flammability Limit - Upper(%) 1.8

Flammability Limit - Lower(%) 10.0

# SECTION 10: STABILITY AND REACTIVITY

## 10.1. Reactivity

Stable under normal temperature conditions.

## 10.2. Chemical stability

Stable under normal temperature conditions.

# 10.3. Possibility of hazardous reactions

None known

# 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition., Increase in temperature to greater than 50 degrees will cause rise in internal pressure with likelihood of bursting/explosion.

MSDS: K007 - SILICONE LUBRICANT language: english Page 3 of 5





#### 10.5. Incompatible materials

Strong oxidising substances.

#### 10.6. Hazardous decomposition products

Fire creates:, Toxic gases/vapours/fumes of:, Carbon monoxide (CO)., Carbon dioxide (CO2).

#### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological effects

Toxicological information No toxicological data is available for this mixture, however data can be provided for specific raw materials upon

request.

Inhalation High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and

vomiting., Gas or vapour displaces oxygen available for breathing (asphyxiant)., Unconsciousness.

Ingestion May cause burns in mucous membranes, throat, oesophagus and stomach., May cause stomach pain or vomiting.

Skin contact No specific health warnings noted.

Eye contact Irritation of eyes and mucous membranes.

## SECTION 12: ECOLOGICAL INFORMATION

#### 12.1. Toxicity

Not regarded as dangerous for the environment.

#### 12.2. Persistence and degradability

Degradability The product is expected to be biodegradable.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

## 12.4. Mobility in soil

Mobility: The product is insoluble in water and will sediment in water systems.

## 12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or PvB substances

#### 12.6. Other adverse effects

None known

## SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard., Dispose of waste and residues in accordance with local authority requirements.

# SECTION 14: TRANSPORT INFORMATION

# 14.1. UN number

 UN No. (ADR/RID/ADN)
 1950

 UN No. (IMDG)
 1950

 UN No. (ICAO)
 1950

#### 14.2. UN proper shipping name

Proper Shipping Name: AEROSOLS, FLAMMABLE

MSDS: K007 - SILICONE LUBRICANT language: english Page 4 of 5





# K007

#### 14.3. Transport hazard class(es)

ADR/RID/ADN Class 2 Class Code:5F Label: 2.1

IMDG Class 2.1 ICAO Class/Division 2.1

Transport Labels Not Applicable

14.4. Packing group

IMDG Packing group N/A ICAO Packing group N/A

14.5. Environmental hazards

Environmentally Hazardous substance/Marine Pollutant No.

14.6. Special precautions for user

Tunnel Restriction Code n/a

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not relevant

**EU** Legislation

#### SECTION 15: REGULATORY INFORMATION

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

UK Regulatory References The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments. Environmental Listing Rivers (Prevention of Pollution) Act 1961., Control of Pollution (Special Waste Regulations) Act 1980.

Statutory Instruments

Control of Substances Hazardous to Health., The Chemicals (Hazard Information and Packaging for Supply)

Regulations 2009 (S.I 2009 No. 716).

Approved Code Of Practice Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes Workplace Exposure Limits EH40., Introduction to Local Exhaust Ventilation HS(G)37., CHIP for everyone HSG

(108)

System of specific information relating to Dangerous Preparations. 2001/58/EC., Dangerous Preparations Directive 1999/45/EC., Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments., Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of

substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

The Complete of Demonstrate Considerated and United Trees

National Regulations The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007).

## 15.2. Chemical Safety Assessment

No chemical assessment has been carried out as this Safety Data Sheet is for a mixture

#### SECTION 16: OTHER INFORMATION

General information

The following risk phrases relate to the raw materials in the product and not the product itself:-

**Revision Comments** 

Safety Data Sheet revised to be in accordance with EU Regulation No 453/2010 - REACH Regulations.

Revision Date 05/03/2013 Revision 10

Risk Phrases In Full R12 Extremely flammable.] R10 Flammable., R53 May cause long-term adverse effects in the aquatic

environment., R66 Repeated exposure may cause skin dryness or cracking., R65 Harmful: may cause lung damage

 $if \ swallowed. |$ 

Hazard Statements In Full H224 Extremely flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.H411 Toxic to aquatic life with long lasting effects.

MSDS: K007 - SILICONE LUBRICANT language: english Page 5 of 5