



G001 SELCOTE

1. IDENTIFICATION OF THE PREPARATION AND COMPANY

PRODUCT CODE: G001
PRODUCT NAME: SELCOTE
MANUFACTURER: Selden Research Limited
Staden Lane
Ashbourne Road
Buxton
Derbyshire
SK17 9RZ

TELEPHONE: 01298 26226
FAX: 01298 26540
EMAIL: safety@selden.co.uk

2. COMPOSITION/INFORMATION ON INGREDIENTS

NAME CAS No.:	EINECS Nr.:	CLASSIFICATION	CONTENT
WHITE SPIRIT 64742-82-1	265-185-4	Xn;R65. N;R51/53. R10,R66.	30-60 %

The full text for all R-Phrases are displayed in Section 16

3. HAZARDS IDENTIFICATION

R10 Flammable., R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment., R66 Repeated exposure may cause skin dryness or cracking.

4. FIRST AID MEASURES

INHALATION: Move the exposed person to fresh air at once. Get medical attention. Provide rest, warmth and fresh air. For breathing difficulties oxygen may be necessary.

INGESTION: DO NOT INDUCE VOMITING!, If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Drink plenty of water. Get medical attention immediately!, Provide rest, warmth and fresh air.

SKIN: Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing.

EYES: Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Fire can be extinguished using: , Foam. Dry chemicals, sand, dolomite etc.

SPECIAL FIRE FIGHTING PROCEDURES: Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out.

6. ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS: Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer.

7. HANDLING AND STORAGE

USAGE PRECAUTIONS: Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS: Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

USAGE DESCRIPTION: Flammable liquid storage.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

PROTECTIVE EQUIPMENT:





G001 SELCOTE

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Liquid
COLOUR:	Light (or pale), to, Amber
ODOUR:	Kerosene.
DENSITY/SPECIFIC GRAVITY(g/ml)	0.89 - 0.94
FLASH POINT (°C):	38 (white spirit) CC (Closed)

10. STABILITY AND REACTIVITY

STABILITY:	Stable under normal temperature conditions.
CONDITIONS TO AVOID:	Avoid contact with strong oxidisers.
HAZARDOUS COMPOSITION PRODUCTS:	Fire creates:, Toxic gases/vapours/fumes of:, Carbon monoxide (CO). Carbon dioxide (CO2).

11. TOXICOLOGY INFORMATION

INHALATION:	Prolonged inhalation of high concentrations may damage respiratory system. Drowsiness, dizziness, disorientation, vertigo.
INGESTION:	Harmful: may cause lung damage if swallowed.
SKIN CONTACT:	Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.
EYE CONTACT:	May cause severe irritation to eyes.

12. ECOLOGICAL INFORMATION

ECOTOXICITY:	Toxic to aquatic organisms., May cause long term adverse effects in the aquatic environment.
--------------	--

13. DISPOSAL CONSIDERATIONS

DISPOSABLE METHODS:	Dispose of waste and residues in accordance with local authority requirements., Do not allow runoffs! This chemical is toxic to organisms in water.
---------------------	---

14. TRANSPORT INFORMATION

LABEL FOR CONVEYANCE:



UN No ROAD:	1263
UK ROAD PACK GR.:	III
ADR CLASS NO.:	3
PROPER SHIPPING NAME I:	PAINT(Resin in white spirit)
UN No SEA:	1263
UN NO. AIR:	1263



G001 SELCOTE

15. REGULATORY INFORMATION

LABEL FOR SUPPLY:



RISK PHRASES:

R10 Flammable. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R66 Repeated exposure may cause skin dryness or cracking.

SAFETY PHRASES:

S2 Keep out of the reach of children, S16 Keep away from sources of ignition - No smoking. S51 Use only in well-ventilated areas. S24/25 Avoid contact with skin and eyes. S61 Avoid release to the environment. Refer to special instructions/safety data sheets. S23A Do not breathe gas/fumes/vapour/spray.

STATUTORY INSTRUMENTS:

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE:

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES:

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16. OTHER INFORMATION

USER NOTES:

The following risk phrases relate to the raw materials in the product and not the product itself:-

REVISION DATE:

09/05/2005

REV. NO./REPL. SDS GENERATED:

9

R-PHRASES (Full Text):

R10 Flammable., R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment., R66 Repeated exposure may cause skin dryness or cracking., R65 Harmful: may cause lung damage if swallowed.]