

# SAFETY DATA SHEET

## SELKIL HSE 4828 - DISCONTINUED

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name SELKIL HSE 4828 - DISCONTINUED

Product number K002

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Fly Killer

#### 1.3. Details of the supplier of the safety data sheet

Supplier **SELDEN RESEARCH LIMITED**  
STADEN LANE  
BUXTON  
DERBYSHIRE  
SK17 9RZ  
UNITED KINGDOM

Tel. 01298 26226  
Fax. 01298 26540  
email safety@selden.co.uk

#### 1.4. Emergency telephone number

National emergency telephone number Mon to Fri 8.30am to 5.00pm - 01298 26226

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification

##### Physical hazards

Aerosol 1 - H222, H229

##### Health hazards

Elicitation (Skin Sens.)

##### Environmental hazards

Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

##### Classification (67/548/EEC or 1999/45/EC)

Carc. Cat. 3;R40. F+;R12. N;R50/53.

#### 2.2. Label elements

##### Pictogram



##### Signal word

Danger

##### Hazard statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: may burst if heated  
H410 Very toxic to aquatic life with long lasting effects.  
EUH208 Contains PERMETHRIN. May produce an allergic reaction.

##### Precautionary statements

## SELKIL HSE 4828 - DISCONTINUED

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P273 Avoid release to the environment.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

### 2.3. Other hazards

PRESSURISED CONTAINER - increase in temperature to greater than 50C will cause internal pressure to rise potentially causing bursting/explosion.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>BUTANE</b>	<b>30-60%</b>
CAS number: 106-97-8    EC number: 203-448-7	
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Gas 1 - H220	F+;R12
Press. Gas, Liquefied - H280	
<b>PROPAN-2-OL</b>	<b>5-10%</b>
CAS number: 67-63-0    EC number: 200-661-7	
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Liq. 2 - H225	F;R11 Xi;R36 R67
Eye Irrit. 2 - H319	
STOT SE 3 - H336	
<b>PIPERONYL BUTOXIDE</b>	<b>1-5%</b>
CAS number: 51-03-6    EC number: 200-076-7	
M factor (Acute) = 1    M factor (Chronic) = 1	
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Aquatic Acute 1 - H400	N;R50/53.
Aquatic Chronic 1 - H410	
<b>TETRAMETHRIN</b>	<b>&lt;1%</b>
CAS number: 7696-12-0    EC number: 231-711-6	
M factor (Acute) = 1    M factor (Chronic) = 1	
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Aquatic Acute 1 - H400	N;R50/53.
Aquatic Chronic 1 - H410	

## SELKIL HSE 4828 - DISCONTINUED

### PERMETHRIN

<1%

CAS number: 52645-53-1 EC number: 258-067-9

M factor (Acute) = 1000 M factor (Chronic) = 1000

#### Classification

Acute Tox. 4 - H302

Acute Tox. 4 - H302

Acute Tox. 4 - H332

Skin Sens. 1 - H317

Skin Sens. 1 - H317

Aquatic Acute 1 - H400

Aquatic Chronic 1 - H410

#### Classification (67/548/EEC or 1999/45/EC)

Xn;R20/22 R43 N;R50/53

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Move affected person to fresh air at once. Keep affected person warm and at rest. Get medical attention immediately.

#### Ingestion

Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention.

#### Skin contact

Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

#### Eye contact

If liquid has entered the eyes, proceed as follows. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### 4.2. Most important symptoms and effects, both acute and delayed

#### General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

#### Inhalation

Vapours may cause headache, fatigue, dizziness and nausea.

#### Ingestion

May cause chemical burns in mouth and throat. May cause stomach pain or vomiting.

#### Skin contact

Prolonged or repeated contact with skin may cause irritation, redness and dermatitis.

#### Eye contact

Irritation of eyes and mucous membranes.

### 4.3. Indication of any immediate medical attention and special treatment needed

#### Notes for the doctor

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

### 5.2. Special hazards arising from the substance or mixture

#### Specific hazards

Containers can burst violently or explode when heated, due to excessive pressure build-up.

### 5.3. Advice for firefighters

## SELKIL HSE 4828 - DISCONTINUED

### Protective actions during firefighting

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

### Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### Personal precautions

For personal protection, see Section 8.

### 6.2. Environmental precautions

#### Environmental precautions

Any spillage needs to be contained and not allowed to enter water courses

### 6.3. Methods and material for containment and cleaning up

#### Methods for cleaning up

Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. If leakage cannot be stopped, evacuate area.

### 6.4. Reference to other sections

#### Reference to other sections

For personal protection, see Section 8. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Usage precautions

Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Storage precautions

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

### 7.3. Specific end use(s)

#### Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

#### Usage description

See product label for detailed usage and instructions.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m<sup>3</sup>

##### PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

#### Ingredient comments

WEL = Workplace Exposure Limits

## 8.2. Exposure controls

### Protective equipment



### Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

### Eye/face protection

The following protection should be worn: Chemical splash goggles.

### Hand protection

Use protective gloves.

### Other skin and body protection

General workwear only

### Hygiene measures

DO NOT SMOKE IN WORK AREA!

---

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

Aerosol.

#### Flash point

- 74°C

#### Upper/lower flammability or explosive limits

: 1.8

#### Auto-ignition temperature

+ 405°C

#### Comments

Information given relates to total aerosol container contents.

### 9.2. Other information

#### Other information

None.

---

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

May react with other cleaning chemicals. For specific reactions refer to Section 10.5

### 10.2. Chemical stability

#### Stability

Stable at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

---

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

## SELKIL HSE 4828 - DISCONTINUED

### Toxicological effects

No toxicological data is available for this mixture, however data can be provided for specific raw materials upon request.

### Inhalation

May cause respiratory system irritation. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.

### Ingestion

May cause burns in mucous membranes, throat, oesophagus and stomach. May cause stomach pain or vomiting.

### Skin contact

Prolonged or repeated exposure may cause severe irritation. Product has a defatting effect on skin. Repeated exposure may cause skin dryness or cracking. May cause allergic contact eczema.

### Eye contact

Irritation of eyes and mucous membranes.

## SECTION 12: Ecological Information

### Ecotoxicity

Harmful to aquatic organisms. May cause long term adverse effects in the aquatic environment.

#### 12.1. Toxicity

Aquatic toxicity has not been carried out on this product. Data for raw materials contained in this product, when available, can be provided when necessary.

#### 12.2. Persistence and degradability

##### Persistence and degradability

The product is biodegradable.

#### 12.3. Bioaccumulative potential

The product does not contain any substances expected to be bioaccumulating.

#### 12.4. Mobility in soil

##### Mobility

The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

#### 12.5. Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

#### 12.6. Other adverse effects

None known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal methods

Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

## SECTION 14: Transport information

### 14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

### 14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS, FLAMMABLE
--------------------------------	---------------------

## SELKIL HSE 4828 - DISCONTINUED

Proper shipping name (IMDG) AEROSOLS, FLAMMABLE

Proper shipping name (ICAO) AEROSOLS, FLAMMABLE

Proper shipping name (ADN) AEROSOLS, FLAMMABLE

### 14.3. Transport hazard class(es)

ADR/RID class 2

IMDG class 2.1

ICAO class/division 2.1

### 14.4. Packing group

### 14.5. Environmental hazards

### 14.6. Special precautions for user

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **National regulations**

Control of Substances Hazardous to Health Regulations 2002 (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

#### **EU legislation**

System of specific information relating to Dangerous Preparations. 2001/58/EC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

#### **Guidance**

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG228. Approved Classification and Labelling Guide (Sixth edition) L131.

### 15.2. Chemical safety assessment

No chemical assessment has been carried out as this Safety Data Sheet is for a mixture.

## **SECTION 16: Other information**

#### **General information**

The following risk phrases relate to the raw materials in the product and not the product itself:-

#### **Revision comments**

Safety Data Sheet revised to be in accordance with EU Regulation No 453/2010 - REACH Regulations.

Revision date 30/12/2014

Revision 9

#### **Risk phrases in full**

R11 Highly flammable

R12 Extremely flammable.

R20/22 Harmful by inhalation and if swallowed.

R36 Irritating to eyes.

R40 Limited evidence of a carcinogenic effect.

R43 May cause sensitisation by skin contact.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

## SELKIL HSE 4828 - DISCONTINUED

### Hazard statements in full

- EUH208 Contains PERMETHRIN. May produce an allergic reaction.
- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H229 Pressurised container: may burst if heated
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.